



Australia

KINGHITTER

THE HEAVYWEIGHT IN POSTDRIVERS

**'Punches well
above its weight'**



**Series II Expander with Terminator
Base & Compulsory Safety Guarding**

www.kinghitter.com

SERIES II - HD BEAM

KINGHITTER Heavy Duty Beam

3.8m Beam
250kg Hammer

**Packs the
Professional
Punch**

Terminator Base
- Converts to Side Mount 900mm Side Shift



Series II Rear Mount - Rotation Angles



Compulsory Safety Guards

Series II Mounted on Terminator Base



Series II Rear Mount (Shown without Safety Guards)

Testimonial

"A postdriver that makes fencing fast, safe and accurate and especially with the accessories like the rock spike extractor kit you can't get a better machine."

Specifications

Kinghitter™ Series II **3.8m Beam** **250kg Hammer**

- 3 Point Linkage – Rear Mounted
- The World's Finest Post Driver with Double Thickness Steel on the Main Beam / Proven World Over
- Suitable for Construction Sites
- Ideal for Farmers, Ranchers, Vineyards, Contractors, Freeway Construction
- Mounts to Tractors, Skid Steer Loaders, Excavators, Back Hoes, Barges, Pontoons
- Drives up to 300mm dia Posts
- Standard Safety Weight Stop
- Freestanding in most conditions
- Standard Heavy Duty Safety Post Cap

- Standard Safety Hammer Lock
- Compulsory Safety Guarding and Interlocked Operating Controls

Series II Optional Extras

- Pilot Auger Kit
- Rock Spike Extractor
- Rock Spike Extractor Post Cap
- Rock Spike Combo Auger Unit
- 500mm Side Shift Multi-Shift Base. (This also can be purchased with a 150mm Back Shift as well)
- Terminator Base 900mm Side Shift. This makes a Series II Side Mounted.
- Top Link Extension Bracket
- Super Side Shift – 500mm Side Shift Ram

SERIES II - EXPANDER

KINGHITTER Expander

3.1m to 5.1m Mast
340kg Hammer

For its height,
punches well
above its weight

Testimonial

“The expander is great to get in and out of places and the rock spike a must. Now I can go anywhere and drive a post into anything.”



Shown without Safety Guards

Skid Steer Mounted - Closed Position



Shown without Safety Guards

Skid Steer Mounted - Post Driving Position



Compulsory Safety Guards

Series II Expander Rear Mounted with Guarding & Auger



*Series II Expander
with Compulsory Safety Guarding & Auger*

Specifications

Kinghitter™ Series II Expander **3.1m to 5.1m Expanding Mast** **340kg Hammer**

- Telescopic Mast
- Closed Position 3.1m -
Open Position 5.1m
- 3 Point Linkage Mounted
- Mounts to Tractor, Skid Steer, Loader,
Excavator, Barge & Pontoon
- Safety Hammer Lock
- **Orkot** Slides on Hammer & Postcap
- Storage and Transport Height - 3.1m
- **Compulsory Safety Guarding and Interlocked Operating Controls**

Kinghitter™ Series II Expander **Optional Extras**

- Pilot Auger Kit
- Rock Spike Extractor Kit
- Rock Spike Combo Kit
- Terminator Base - 900mm Side Shift,
includes 5 cu.ft Toolbox

SERIES III - HD BEAM

KINGHITTER Heavy Duty Beam

3.8m Beam
250kg Hammer

The
Heavyweight
Not for the
Light-Hearted

Testimonial

**"A real post pounder
that will drive posts in
all types of terrain."**

Specifications

Kinghitter™ Series III **3.8m Beam, 250kg Hammer**

- 3 Point Linkage – Side Mounted
- The World's Finest Post Driver with Double Thickness Steel on Main Beam
- Ideal for Farmers, Ranchers, Vineyards, Contractors, Freeway Construction
- Mounts to Tractors, Skid Steers, Back Hoes
- Standard 450mm Hydraulic Side Shift
- Drives up to 300mm dia Posts
- Standard Safety Weight Stop
- Standard Heavy Duty Safety Post Cap
- Standard Safety Hammer Lock
- **Compulsory Safety Guarding and Interlocked Operating Controls**

Series III Optional Extras

- Hydraulic Auger
- Hydraulic Rock spike
- Combo Spike – Auger Unit
- Full Guarding Optional
- Orchard Base 5'7" width



Shown without Safety Guards

Series III Side Mount - 450mm side movement

SERIES III - EXPANDER

KINGHITTER EXPANDER

3.1m to 5.1m Mast
340kg Hammer



Optional Rock Spike Accessory

Specifications

Kinghitter™ Series III Expander **3.1 to 5.1m Expanding Mast** **340kg Hammer**

- Telescopic Mast
- Closed Position 3.1m - Open Position 5.1m
- 3 Point Linkage Mounted
- Mounts to Tractor, Skid Steer, Loader, Excavator, Barge & Pontoon
- Standard 450mm Hydraulic Side Shift
- Safety Hammer Lock
- **Orkot** Slides on Hammer & Postcap
- Storage and Transport Height - 3.1m
- **Compulsory Safety Guarding and Interlocked Operating Controls**

Kinghitter™ Series III Expander **Optional Extras**

- Hydraulic Auger
- Hydraulic Rock Spike
- Combo Spike and Auger Unit



Series III Expander (Compulsory Safety Guards)

19 NEW SAFETY FEATURES

Australian Work Cover Compliant



KINGHITTER

have 19 NEW Safety Features added to Kinghitter Series II, III, II Expander and III Expander that are additional to the compulsory Safety Guards to ensure maximum protection for the operator. In addition to these please read the 'Committed to safety first' on the back of this brochure.

- 1 Main Guard travels up and down with Post Cap** keeping hands out above and below strike zone
- 2 Guards** to prevent hands contacting with nip points on wire rope
- 3 Guard** to protect body from broken posts while ramming
- 4 Weight stop** included for safety operator
- 5 Hydraulic Hoses** have a safety factor above 4:1
- 6 Retaining Plate** on main swivel pin
- 7 Wire Rope** has swaged end on lifting the hammer
- 8 Rubber Sleeve** protects rope, bolt and collar
- 9 Safety Signs** positioned on both sides warning operator of serious safety risks
- 10 Information** on the total (mass) weight of the post driver on mast
- 11 Operating Instructions and practical hints with postdriver** supplied in water proof receptacle
- 12 Up and Down Lever** orientated differently from other levers
- 13 Valve Bank Handle Guard**
- 14 All Controls** are clearly identified
- 15 All Control Levers** return to neutral when released
- 16 Extra Hydraulic Control Lever** keeps both hands out of strike zone while operating
- 17 Interlock Lever** hydraulic control lever to control the drop speed of weight in operation
- 18 Free Standing Leg** on hard surface
- 19 Safety Bolt** in bottom link arms. Prevents post driver falling on operator if top link fails.



Terminator Base Side Shift with Compulsory Safety Guard



Safety Signs

Rubber Sleeve



Information on Total Mass Weight



Valve Bank

SPECIFICATIONS

Specifications	Series II	Series III	II EXPANDER	III EXPANDER
MOUNTING	Category II	Category II	Category II	Category II
MAST LENGTHS	3.8m	3.8m	3.1m to 5.1m	3.1m to 5.1m
HAMMERS	250kg	250kg	340kg	340kg
IMPACT AT FULL STROKE	3.8m 80,000 PSI	3.8m 80,000 PSI	3.1m-5.1m 100,000 PSI	3.1m-5.1m 100,000 PSI
TILT FRONT / BACK	10° / 20°	30° / 30°	10° / 30°	30° / 30°
TILT SIDE / SIDE	20° / 20°	25° / 45°	20° / 28°	28° / 40°
LEGS	Adjustable	Adjustable	Adjustable	Adjustable
TOP LINK	Hydraulic	Hydraulic	Hydraulic	Hydraulic
ANGLE ADJUSTMENT	Hydraulic	Hydraulic	Hydraulic	Hydraulic
SIDE SHIFT	Yes/Optional	450mm Standard Hydraulic	Yes/Optional	450mm Standard Hydraulic
SAFETY POST CAP	Standard	Standard	Standard	Standard
SAFETY GUARD	Standard	Standard	Standard	Standard
SAFETY HAMMER LOCK	Standard	Standard	Standard	Standard
MAX. POST HEIGHT	3.1m post	3.1m post	4.25m post	4.25m post
MIN. HYDRAULIC PSI	1800 PSI	1800 PSI	2200 PSI	2200 PSI
VOLUME OIL / MIN. AV	8 GPM	8 GPM	10 GPM	10 GPM
STORAGE HEIGHT	3.8m	3.8m	3.1m	3.1m
SHIPPING WEIGHT (GUIDE ONLY)	637kg	1,035kg	925kg	1,302kg
SHIPPING VOLUME	From 21 cu.ft	From 46 cu.ft	From 66 cu.ft	From 85 cu.ft
PILOT AUGER KIT	Yes/Optional	Yes/Optional	Yes/Optional	Yes/Optional
ROCK SPIKE EXTRACTOR	Yes/Optional	Yes/Optional	Yes/Optional	Yes/Optional
ROCK SPIKE COMBO AUGER UNIT	Yes/Optional	Yes/Optional	Yes/Optional	Yes/Optional
TERMINATOR BASE 900mm SIDE SHIFT	Yes/Optional	No	Yes/Optional	No
MULTI SHIFT BASE 150mm BACK SHIFT 500mm SIDE SHIFT	Yes/Optional	No	Yes/Optional	No

Kinghitter™ – The Right Tool for the Right Job

Series II -	Construction, Farming, Ranches, Game Fencing, Hire Company, Skid Steer Loaders, Retaining Walls
Series III -	Orchards, Fencing Contractors, Freeway Guard Rails, Vineyards, Game Fencing, Farming Ranches
Expander SII & SIII -	Great for transporting on trucks, Contractors, Councils, Construction Sites, Under Trees
Rock Spike -	Stony Rocky Conditions, Pilot hole stops posts being damaged, leaving tighter construction
Combo Auger -	1100lb Down Pressure, Limestone, Sandstone, Iron Sand, Heavy Clays
Pilot Auger -	550lb Down Pressure, Limestone, Sandstone, Heavy Clays
Rock Spike Postcap -	Shelf rock and hard conditions. Required when using Rock Spike
Orchard Base -	Series 3 fits down 7' rows. Also can be used on Skid Steer Loaders, Guard Rail Construction

Fairbrother Industries - Committed to Safety 1st

- **Compulsory Safety Guarding with Interlocking Operating Controls**
- Study the Operators Manual, Watch the Assembly & Safety Video, and follow the instructions on the Safety Decal
- Offset controls lets the operator stand safely to the side of the driver
- Post Cap guides the post correctly & protects the operator from impact
- Never stand in front of the driver, always stand to one side of the post being driven
- Use the correct Post Cap or T Post holder to hold the post.
- Change the valve to suit open or closed centre hydraulics
- Always check for underground and overhead obstacles (wires, pipes etc...)
- Make sure all legs are positioned firmly on the ground
- Never use the maximum force of the driver until you are sure the post is being driven straight
- Keep hands away from the top of the post at all times.
- Use the right horse power tractor unit to suit the driver.
- Do not operate the post driver for other uses.
- Use caution when driving small diameter wood and steel posts.
- Wear appropriate Safety equipment (Ear Muffs, Safety Glasses, and Hard-Hat).
- Consider the operating environment (steep slopes can cause roll overs).

DISTRIBUTED BY

FAIRBROTHER
INDUSTRIES LIMITED.

Phone: 1800 256 753
Web: www.kinghitter.com

